

CLAIMS

I claim:

- 5 1. A method for transmitting Packetized SCSI
Protocol command blocks comprising:
 transmitting a first Packetized SCSI
Protocol command block; and
 transmitting a second Packetized SCSI
10 Protocol command block with a substantially zero
latency following transmission of said first
Packetized SCSI Protocol command block.
2. The method of Claim 1 wherein transmitting
15 said first Packetized SCSI Protocol command block
further comprises:
 transmitting at least one byte in said first
Packetized SCSI Protocol command block directly
from a storage location of said at least one
20 byte.
3. The method of Claim 2 wherein said storage
location of said at least one byte is within a stored
first hardware I/O control block.
25
4. The method of Claim 3 wherein said at least
one byte is in a logical unit number field of said
first Packetized SCSI protocol command block.
- 30 5. The method of Claim 2 wherein said storage
location of said at least one byte is within a pointer
register of a host adapter integrated circuit.
6. The method of Claim 3 wherein said stored
35 first hardware I/O control block includes a pointer to
a storage location of a second hardware I/O control

block, and further wherein said second hardware I/O control block includes information used directly in said transmitting said second Packetized SCSI Protocol command block.

5

7. A SCSI initiator system comprising:

a target execution queue containing at least two hardware I/O control blocks for a SCSI target wherein the target execution queue is stored in a memory; and

10

a Packetized SCSI Protocol hardware packet engine coupled to the target execution queue, wherein the Packetized SCSI Protocol hardware packet engine transmits a Packetized SCSI Protocol command block for each hardware I/O control block in said target execution queue with substantially zero latency between transmission of adjacent Packetized SCSI Protocol command blocks.

15

20

8. The SCSI initiator system of Claim 7 wherein the Packetized SCSI protocol hardware packet engine further comprise:

a hardware information unit transfer controller having a start input line and a data out phase input line wherein the hardware information unit transfer controller sequences hardware generation of the Packetized SCSI Protocol command blocks upon receiving an active signal on the start input line and an active signal on the data out phase input line.

25

30

9. The SCSI initiator system of Claim 8 wherein the Packetized SCSI protocol hardware packet engine further comprises:

35

5 a hardware header generator coupled to the
hardware information unit transfer controller,
wherein the hardware header generator generates
fields in a command L_Q information unit in
response to signals from the hardware information
unit transfer controller.

10 10. The SCSI initiator system of Claim 8 wherein
the Packetized SCSI protocol hardware packet engine
further comprises:

15 a hardware body generator coupled to the
hardware information unit transfer controller,
wherein the hardware header generator generates
fields in a command information unit in response
to signals from the hardware information unit
transfer controller.

20 11. The SCSI initiator system of Claim 9 wherein
the Packetized SCSI protocol hardware packet engine
further comprises:

25 a hardware body generator coupled to the
hardware information unit transfer controller,
wherein the hardware body generator generates
fields in a command information unit in response
to signals from the hardware information unit
transfer controller.

30 12. The SCSI initiator system of Claim 9 further
comprising a hardware I/O control block pointer
register coupled to the hardware header generator.

35 13. The SCSI initiator system of Claim 10
further comprising a hardware I/O control block
pointer register coupled to the hardware body
generator.

14. The SCSI initiator system of Claim 11 further comprising a hardware I/O control block pointer register coupled to the hardware header generator.

5

15. The SCSI initiator system of Claim 14 wherein the hardware I/O control block pointer register is also coupled to the hardware body generator.

10

16. A Packetized SCSI Protocol hardware packet engine comprising:

15 a hardware information unit transfer controller having a start input line and a data out phase input line wherein the information unit transfer controller sequences hardware generation of a Packetized SCSI Protocol packet byte stream upon receipt of an active signal on the start input line and an active signal on the data out phase input line; and

20

25 a hardware header generator coupled to the hardware information unit transfer controller, wherein the hardware header generator generates fields in a command L_Q information unit in response to signals from the hardware information unit transfer controller.

25

17. The Packetized SCSI Protocol hardware packet engine of Claim 16 further comprising:

30 a hardware body generator coupled to the hardware information unit transfer controller, wherein the hardware header generator generates fields in a command information unit in response to signals from the hardware information unit transfer controller.

35

18. The Packetized SCSI Protocol hardware packet engine of Claim 17 further comprising a hardware I/O control block pointer register coupled to the hardware header generator.

5

19. The Packetized SCSI Protocol hardware packet engine of Claim 17 further comprising a hardware I/O control block pointer register coupled to the hardware body generator.

10

20. The Packetized SCSI Protocol hardware packet engine of Claim 17 further comprising a hardware I/O control block pointer register coupled to the hardware header generator.

15

21. A method for generating a Packetized SCSI Protocol command block comprising:

transferring information required in a command information unit and available in a hardware I/O control block directly from the hardware I/O control block; and

20

transferring information required in the command information unit but unavailable in the hardware I/O control block directly from a register.

25

09842750 042501
F05240 052480